


Everest G12R Series 605-640W

132-cell Bifacial HJT Half Cell
Double-glass Solar Module



HJT-0BB Technology

Shorter current transport path, better low-light performance, and higher power generation.



Sealing with PIB

Stronger moisture resistance, greater air impermeability to extend module lifespan.




Full Scenarios Coverage

Suitable for all scenario, especially C&I, residential, and ground applications, lower BOS cost, lower LCOE.



Complete System and Product Certifications:

- IEC61215, IEC61730
- ISO9001: 2015 Quality Management System
- ISO14001: 2015 Environment Management System
- ISO45001: 2018 Occupational Health and Safety
- IEC62941: 2019 Terrestrial Photovoltaic (PV) Modules-quality System for PV Module Manufacturing
- IEC/TS62994: 2019 Photovoltaic (PV) Modules Through the Life Cycle-environmental Health and Safety (EH&S) Risk Assessment-general Principles and Nomenclature



* First year power degradation $\leq 1\%$
 * Annual power degradation (2-30 year) $\leq 0.3\%$
 * Power output until the 30th year $\geq 90.3\%$


HSN-210R-B132 605-640W

132-Half-Cell Bifacial HJT Module

- BloombergNEF Tier 1 PV module manufacturer
- Reinsurance underwritten by Ariel Re



Engineering Drawings

Unit: mm



I-V Curve

(HSN-210R-B132DS620)



Temperature Characteristics

Temperature Coefficient of Pmax	-0.24%/°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	+0.04%/°C

Operating Conditions

Nominal Operating Cell Temp.	44±2°C
Operating Temperature	-40~+85°C
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	30A
Tolerance of Pmax	0~+3%
Power Selection	0~+5W
Bifaciality	90±5%
Safety Class	Class II

Mechanical Characteristics

Cell Type	HJT
No. of Cells	132 (6x22)
Dimensions	2382 x 1134 x 30 mm
Weight	32kg
Junction Box	IP68
Cable	4mm ² ; +350/-250mm or customized; UV resistant
Connector	MC4 / MC4-Evo2 / MC4-Evo2A / PV-H4 / Z4S-abcd / PV-ZH202B
Frame	Glass fiber reinforced polyurethane frame
Max Static Load (front side/rear side)	5400Pa / 2400Pa
Glass	Dual glass, 2.0mm

Electrical Characteristics

STC

HSN-210R-B132	DS605	DS610	DS615	DS620	DS625	DS630	DS635	DS640
Maximum Power (Pmax/W)	605	610	615	620	625	630	635	640
Module Efficiency (%)	22.4	22.6	22.8	23.0	23.1	23.3	23.5	23.7
Voltage at Pmax (Vmp/V)	40.78	40.85	40.96	41.05	41.14	41.23	41.32	41.41
Current at Pmax (Imp/A)	14.85	14.95	15.03	15.12	15.21	15.30	15.39	15.47
Open Circuit Voltage (Voc/V)	48.85	48.94	49.05	49.15	49.25	49.34	49.43	49.52
Short Circuit Current (Isc/A)	15.66	15.76	15.86	15.96	16.06	16.16	16.26	16.36

STC: AM1.5, 1000W/m², 25°C.

BNPI

Maximum Power (Pmax/W)	678	684	689	695	700	706	712	717
Voltage at Pmax (Vmp/V)	40.92	40.99	41.10	41.19	41.28	41.37	41.46	41.55
Current at Pmax (Imp/A)	16.58	16.69	16.78	16.88	16.98	17.08	17.18	17.27
Open Circuit Voltage (Voc/V)	49.02	49.11	49.22	49.32	49.42	49.51	49.60	49.69
Short Circuit Current (Isc/A)	17.56	17.67	17.79	17.90	18.01	18.12	18.24	18.35

BNPI: AM1.5, 1000W/m², 135W/m², 25°C.

NOCT

Maximum Power (Pmax/W)	461	465	469	473	477	481	484	488
Module Voltage at Pmax (Vmp/V)	38.92	38.98	39.09	39.18	39.26	39.34	39.42	39.52
Current at Pmax (Imp/A)	11.87	11.95	12.01	12.08	12.16	12.23	12.30	12.36
Open Circuit Voltage (Voc/V)	46.62	46.71	46.82	46.91	47.01	47.09	47.18	47.26
Short Circuit Current (Isc/A)	12.52	12.60	12.68	12.76	12.84	12.92	13.00	13.08

NOCT: AM1.5, 800W/m², 20°C, 1m/s.

Packaging

	40HQ
Modules Per Pallet	36
Pallets Per Container	20
Modules Per Container	720



ANHUI HUASUN ENERGY CO., LTD. All rights reserved © 2020-2024

NO.99 Qingliu Road, Economic and Technological Development Zone, Xuancheng, Anhui, China
 Tel: 0086-563-3318095 www.huasunsolar.com
 sales@huasunsolar.com customerservice@huasunsolar.com

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Anhui Huasun reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.